

DS-K1201AEF

Fingerprint and Card Reader



- A group of messy code encrypted data for the security of fingerprint storage
- Supports RS-485 communication with 19200bps-N-8-1 transmission rate. There are CRC test for the protocol
- Supports EM card reading
- Card induction distance is 30 mm to 100 mm
- Supports multiple authentication modes (card, fingerprint, and card + fingerprint)
- Optical CMOS fingerprint module. The characters of fingerprint can be export to the card reader
- Max. 5000 fingerprints storage
- Adopts the optical fingerprint module, supporting 1:N mode (fingerprint, card + fingerprint) and 1:1 mode (card + fingerprint)
- Fingerprint comparison time: 1:1 \leq 1 s, 1:1000 \leq 1 s; FRR \leq 0.01%, FAR \leq 0.001%
- Communication circuit is designed with optical coupling isolation and noise suppression function
- Built-in buzzer for status indication
- Accurate data and time display provided by built-in electronic clock and watchdog program to ensure the basic function of the terminal
- Tamper-proof function



▪ Specification

Network	
Communication protocol	RS-485
Interface	
TAMPER	1
Capacity	
Fingerprint capacity	5000
Authentication	
Fingerprint module	Optical fingerprint module
Fingerprint comparing mode	1:1/1:N
Card type	EM card
General	
Power supply	12 VDC ± 10%
Working temperature	-40 °C to 70 °C (-40 °F to 158 °F)
Working humidity	10% to 90% (No condensing)
Protective level	IP65
Dimensions	62 mm × 132 mm × 44 mm (2.44" × 5.20" × 1.73")
Installation	Surface mounting
Buzzer	Support

** Exposing the equipment to direct sun light, low ventilation or heat source such as heater or radiator is forbidden (ignorance can cause fire danger).

** For device with fingerprint module, we suggest that do not install the device outdoors.

▪ Available Model

DS-K1201AEF

Distributed by

**HIKVISION®****Headquarters**

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
overseasbusiness@hikvision.com

Hikvision USA
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Australia
T +61-2-8599-4233
salesau@hikvision.com

Hikvision India
T +91-22-28469900
sales@pramahikvision.com

Hikvision Canada
T +1-866-200-6690
sales.canada@hikvision.com

Hikvision Thailand
T +662-275-9949
sales.thailand@hikvision.com

Hikvision Europe
T +31-23-5542770
sales.eu@hikvision.com

Hikvision Italy
T +39-0438-6902
info.it@hikvision.com

Hikvision Brazil
T +55 11 3318-0050
Latam.support@hikvision.com

Hikvision Turkey
T +90 (216)521 7070- 7074
sales.tr@hikvision.com

Hikvision Malaysia
T +601-7652-2413
sales.my@hikvision.com

Hikvision UK & Ireland
T +01628-902140
sales.uk@hikvision.com

Hikvision South Africa
Tel: +27 (10) 0351172
sale.africa@hikvision.com

Hikvision France
T +33(0)1-85-330-450
info.fr@hikvision.com

Hikvision Kazakhstan
T +7-727-9730667
nikia.panfilov@hikvision.ru

Hikvision Vietnam
T +84-974270888
sales.vt@hikvision.com

Hikvision UAE
T +971-4-4432090
salesme@hikvision.com

Hikvision Singapore
T +65-6684-4718
sg@hikvision.com

Hikvision Spain
T +34-91-737-16-55
info.es@hikvision.com

Hikvision Tashkent
T +99-87-1238-9438
uzb@hikvision.ru

Hikvision Hong Kong
T +852-2151-1761
info.hk@hikvision.com

Hikvision Russia
T +7-495-669-67-99
saleru@hikvision.com

Hikvision Korea
T +82-(0)31-731-8817
sales.korea@hikvision.com

Hikvision Poland
T +48-22-460-01-50
info.pl@hikvision.com

Hikvision Indonesia
T +62-21-2933759
Sales.Indonesia@hikvision.com

Hikvision Colombia
sales.colombia@hikvision.com